

技术参数:

插芯:

- 插针数: 1
- 额定电流: 100A
- 额定电压: 830V
- 额定脉冲电压: 8kV
- 污染等级: 3
- 绝缘阻抗: $> 10^{10}\Omega$
- 材料: 聚碳酸酯
- 颜色: RAL 7032 (浅灰色)
- 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- 依据UL 94的阻燃等级: V0
- 可插拔次数: > 500
- 最大绝缘直径: 13mm

插针:

- 接线方式: 冷压连接
- 材料: 铜合金
- 表面处理: 镀银
- 接触电阻: $< 0.3\text{m}\Omega$
- 线径范围: 10-35mm²



Technical specification:

Insters:

- No. of contact: 1
- Rated current: 100A
- Rated voltage: 830V
- Rated impulse voltage: 8kV
- Pollution degree: 3
- Insulation resistance: $> 10^{10}\Omega$
- Material: polycarbonate
- Colour: RAL 7032(light grey)
- Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
- Flammability acc.to UL 94: V0
- Mating cycles: > 500
- Max. insulation diameter: 13mm

Contacts:

- Terminal: crimp terminal
- Material: copper alloy
- Surface: hard-silver plated
- Contact resistance: $< 0.3\text{m}\Omega$
- Wire gauge: 10-35mm²



订货号 Order No.

版本
REV

重量
weight

比例
Scale

产品代号 Part Code

V1.0

8g

1:1

SO-HMK-001-FC



浙江思美克电气科技有限公司
ZHEJIANG SMICO ELECTRICAL TECHNOLOGY CO.,LTD