




技术参数:

- 插芯:
- 插针数: 2+PE
 - 额定电流: 40A
 - 额定电压: 400V
 - 额定脉冲电压: 6kV
 - 污染等级: 3
 - 依据UL/CSA的额定电压: 400V
 - 绝缘阻抗: $> 10^{10}\Omega$
 - 材料: 聚碳酸酯
 - 颜色: RAL 7032 (浅灰色)
 - 温度范围: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - 依据UL 94的阻燃等级: V0
 - 可插拔次数: > 500
- 插针:
- 接线方式: 轴向螺栓连接
 - 材料: 铜合金
 - 表面处理: 镀银
 - 接触电阻: $< 1\text{m}\Omega$
 - 线径范围: $4-10\text{mm}^2(12-8 \text{ AWG})$
 - 拧紧力矩: $1.8\text{N}\cdot\text{m}$
 - 剥线长度: 8-9mm
- 外壳:
- 材料:
 - 塑料外壳: 聚碳酸酯
 - 金属外壳: 锌合金
 - 依据UL94的阻燃等级:
 - 塑料外壳: V0
 - 金属外壳: IP44
 - 防护等级, 联锁状态, IEC 60529:
 - 塑料外壳: IP67
 - 金属外壳: IP44
- IP67(实现螺栓密封)
- 附件:
- 内六角扳手: SW-2*40
 - 编码元件: CODE-Q2

Technical specification:

- Inserts:
- No. of contact: 2+PE
 - Rated current: 40A
 - Rated voltage: 400V
 - Rated impulse voltage: 6kV
 - Pollution degree: 3
 - Rated voltage acc.to UL/CSA: 400V
 - Insulation resistance: $> 10^{10}\Omega$
 - Material: polycarbonate
 - Colour: RAL 7032(light grey)
 - Temperature range: $-40^{\circ}\text{C} - +125^{\circ}\text{C}$
 - Flammability acc.to UL 94: V0
 - Mating cycles: > 500
- Contacts:
- Terminal: axial screw terminal
 - Material: copper alloy
 - Surface: hard-silver plated
 - Contact resistance: $< 1\text{m}\Omega$
 - Wire gauge: $4-10\text{mm}^2(12-8 \text{ AWG})$
 - Tightening torque: $1.8\text{N}\cdot\text{m}$
 - Stripping length: 8-9mm
- Hoods/Housings:
- Material:
 - Plastic hoods/housings: polycarbonate
 - Metal hoods/housings: zinc die-cast
 - Flammability acc.to UL 94:
 - Plastic hoods/housings: V0
 - Degree of protection, acc.to IEC 60529 for coupled connector:
 - Plastic hoods/housings: IP67
 - Metal hoods/housings: IP44
- IP67(is achieved with seal screw)
- Accessories:
- Hex key SW2: SW-2*40
 - Coding element: CODE-Q2

 		订货号 Order No.	
版本 REV	重量 weight	比例 Scale	产品代号 Part Code
V1.0		1:1	SO-HQV-002.2-F
 浙江思美克电气科技有限公司 ZHEJIANG SMICO ELECTRICAL TECHNOLOGY CO.,LTD			